



Provides one-stop service for all your wire brush requirements through your local welding distributor.

WIRE TYPE SELECTION GUIDE

For brush removal of rust, scale, weld spatter, etc.

LIGHT REMOVAL	MEDIUM REMOVAL	HEAVY REMOVAL
USE Crimped Wire, Wheel or Cup Brush	USE Twisted Tuft, Wheel or Cup Brush	USE Cable Twist, Wheel or Cup Brush

WIRE SIZE SELECTION GUIDE

(DIA. IN INCHES)	(DIA. IN INCHES)	(DIA. IN INCHES)
FINE MEDIUM COARSE .005 .0104, .0118	FINE MEDIUM COARSE .014 .016, .020	MEDIUM COARSE .020 .035
FINER FINISH LONGER LIFE	FINER FINISH LONGER LIFE	FINER FINISH LONGER LIFE
FASTER STOCK REMOVAL SHORTER LIFE	FASTER STOCK REMOVAL SHORTER LIFE	FASTER STOCK REMOVAL SHORTER LIFE

TYPICAL BRUSH APPLICATIONS

WELD CLEANING

- PRIOR TO WELDING
- WELD SCALE REMOVAL
- WELD SPATTER REMOVAL

STEEL DESCALING

- BAR AND ROD
- PIPE
- SHEET AND STRIP

PAINT REMOVAL

- ALL STEEL SHAPES
- NAVAL EQUIPMENT
- AIRCRAFT

THESE ARE BUT A FEW OF THE APPLICATIONS POSSIBLE WITH WIRE BRUSHES.

ABOVE WIRE TYPES AND SIZES ARE ALSO AVAILABLE IN STAINLESS STEEL FOR BRUSHING ALUMINUM, MONEL OR STAINLESS STEEL . . . PREVENTS AFTER-RUST.

RUST REMOVAL





- INTERNAL & EXTERNAL PIPE
- STRUCTURAL STEEL
- FLAT STOCK
- SALVAGE WORK—METAL

CLEANING

- STEEL DRUMS
- OIL TANKS

MOULD CLEANING

- FOUNDRY, ETC
- CORE MAKING EQUIPMENT



CRIMPED WIRE

(DIA. IN INCHES)

SERIES	DM	DA	DH
SECTIONS	ONE	TWO	THREE
RUNNING			
FACE WIDTH	NARROW	MEDIUM	WIDE
DIAMETERS	4-12	4-12	4-12
WIRE SIZES	.014-.0118 .0104-.005	.014-.0118 .0104-.005	.014-.0118 .0104-.005
ARBOR SIZE	3/8-2	1/2-2	1/2-2

TWISTED TUFT

SERIES TS (DIA. IN INCHES)

BRUSH DIA.	COARSE	MED.	FINE	ARBOR HOLE
4	.020	.014	.0118	*3/8, 1/2
6	.023, .030	.016	.0118	*1/2, 5/8
8	.023	.016	.0118	5/8, 3/4
10	.016	.014	.0118	3/4, 1
12	.016	.014	.0118	1, 1 1/4

CABLE TWIST

SERIES TC (DIA. IN INCHES)

BRUSH DIA.	COARSE	MED.	FINE	ARBOR HOLE
4	.020	.014	—	*3/8, 1/2
6	.023, .020	.016	—	*1/2, 5/8
8	.023	.016	—	5/8, 3/4

STRINGER BEAD

SERIES QTC (DIA. IN INCHES)

BRUSH DIA.	COARSE	MED.	FINE	ARBOR HOLE
6	.023	—	—	*1/2, 5/8
8	.023	—	—	5/8, 3/4
10	.023	—	—	3/4, 1

*SNAP-OUT REDUCING BUSHING IN PLACE

ANDERSON POWER BRUSHES

ARE ENGINEERED FOR

The Welding Industry

ANDERSON CORPORATION / 1029 SOUTHBRIDGE STREET / WORCESTER 10, MASS.





WIRE CUP BRUSHES



Special Analysis
High Tensile
Wire

TWISTED TUFT

(DIA. IN INCHES)

SERIES	SINGLE ROW (1 ROW)	STAGGER ROW (1 1/2 ROWS)	DOUBLE ROW (2 ROWS)
DIAMETERS	US	UD	UDX
COARSE	3, 4, 5, 6	3, 4, 5, 6	5, 6
MEDIUM	.035	.035	.035
FINE	.020	.020	.020
ARBOR SIZE	5/8-11	5/8-11	5/8-11



Special Analysis
High Tensile
Wire

CABLE TWIST

(DIA. IN INCHES)

SERIES	SINGLE ROW (1 ROW)	STAGGER ROW (1 1/2 ROWS)	DOUBLE ROW (2 ROWS)
DIAMETERS	USC	UDC	UDXC
COARSE	3, 4, 5, 6	3, 4, 5, 6	5, 6
MEDIUM	.035	.035	.035
ARBOR SIZE	.020	.020	.020
	5/8-11	5/8-11	5/8-11



Special Analysis
High Tensile
Wire

CRIMPED WIRE

SERIES UC (DIA. IN INCHES)

BRUSH DIA.	STANDARD COARSE	WIRE SIZES MED.	ARBOR SIZE
4	.020	.014	5/8-11
5	.020	.014	5/8-11
6	.020	.014	5/8-11
8	.020	.014	5/8-11

CHIPPING HAMMER REFILL



SR

CATALOG NO.	TRIM LENGTH	DESCRIPTION
SR-36	1 1/8	3 X 16 ROWS

WIRE END BRUSHES

Special Analysis High Tensile Wire



NS Series

CRIMPED WIRE SOLID END

(DIA. IN INCHES)

DIA.	STANDARD COARSE	WIRE SIZES MED.	FINE	SHANK DIA.
1/2	.020	.0104	.005	1/4
3/4	.020	.0104	.005	1/4
1	.020	.0104	.005	1/4




NH Series

TWISTED TUFT HOLLOW END

(DIA. IN INCHES)

DIA.	STANDARD COARSE	WIRE SIZES MED.	SHANK DIA.
3/4	.020	.014	1/4
1 1/8	.020	.014	1/4


HAND SCRATCH BRUSHES



HB



HS



HPB-307-S

CATALOG NO.	OVER-ALL LENGTH	DESCRIPTION
HB-39	14	3 X 19 ROWS
HB-49	14	4 X 19 ROWS
HS-46	10	4 X 16 ROWS
*HPB-41-S	13	4 X 21 ROWS
*HPB-307-S	8	3 X 17 ROWS

*.005 STAINLESS WIRE FOR ALUMINUM INERT ARC WELDING.

BLOCK BRUSHES



BB

CATALOG NO.	TRIM LENGTH	DESCRIPTION
BB-510	1	5 X 10 ROWS
BB-512	1 1/4	5 X 10 ROWS

ACID SWAB BRUSHES



AB

WIDTH	CATALOG NUMBER
5/8	AB4
1/2	AB5
1/4	AB6

ORDER

Anderson Weld Cleaning Brushes Today
FROM YOUR
WELDING SUPPLY DISTRIBUTOR